

PUMP SPECIFICATIONS

Manufacturer: Gorman Rupp
Size: 4" x 4" NPT - Female
Type: Self Priming, Trash Handling
Casing: Gray Iron 30
Impeller: Semi-Open, 2 Vane, Ductile Iron
Solids: 1-13/16" Spherical
Impeller Shaft: 1045 Carbon Steel
Seal: Oil-Lubricated Mechanical
Wear Plate: 1026 Carbon Steel
Bearings: Open Ball
Hardware: Standard Plated Steel

ENGINE SPECIFICATIONS

Manufacturer: Deutz
Type: 2 Cylinder, Diesel Engine
Cooling: Air
Performance: 27HP @ 2400 RPM
Displacement: 94.8 Cu. In.
Starter: 12V Electric
Fuel Tank: 50 U.S. Gallons
Full Load Operating Time: 48 Hours



FEATURES:

Standard Equipment: 3500# Torsion Axle, Wheel Kit, 205/75/15 Radial Tires
 Lifting Bail, Tongue Jack, Pintle Ring and Battery
Optional Equipment: DOT Trailer Kit, Bulldog Coupler,
 Automatic Liquid Level Control, 90 Deg. Discharge Elbow, Multiple Suction and
 Discharge Fitting Options - Please Ask Your Representative

