

### PUMP SPECIFICATIONS

**Manufacturer:** Gorman Rupp  
**Size:** 6" x 6" NPT - Female  
**Type:** Self Priming, Trash Handling  
**Casing:** Gray Iron 30  
**Impeller:** Semi-Open, 2 Vane, Ductile Iron  
**Solids:** 2-1/2" Spherical  
**Impeller Shaft:** 4150 Alloy Steel  
**Seal:** Oil-Lubricated Mechanical  
**Wear Plate:** 1015 Carbon Steel  
**Bearings:** Open Ball  
**Hardware:** Standard Plated Steel

### ENGINE SPECIFICATIONS

**Manufacturer:** Deutz  
**Type:** 3 Cylinder, Diesel Engine  
**Cooling:** Air  
**Performance:** 34HP @ 1900 RPM  
**Displacement:** 142.2 Cu. In.  
**Starter:** 12V Electric  
**Fuel Tank:** 50 U.S. Gallons  
**Full Load Operating Time:** 31 Hours



### FEATURES:

**Standard Equipment:** 3500# Torsion Axle, Wheel Kit, 205/75/15 Radial Tires  
 Lifting Bail, Tongue Jack, Pintle Ring and Battery  
**Optional Equipment:** DOT Trailer Kit, Bulldog Coupler,  
 Automatic Liquid Level Control, 90 Deg. Discharge Elbow, Multiple Suction and  
 Discharge Fitting Options - Please Ask Your Representative

