

### PUMP SPECIFICATIONS

**Manufacturer:** Gorman Rupp  
**Size:** 12"x10" Flanged  
**Type:** Prime Assisted, Trash Handling  
**Casing:** Ductile Iron 65-45-12  
**Impeller:** Enclosed, 2 Vane Ductile Iron  
**Solids:** 2" Spherical  
**Impeller Shaft:** Alloy Steel 4150M  
**Seal:** Mechanical, Oil Lubricated  
**Wear Ring:** Ductile Iron 65-45-12  
**Bearings:** Oil Lubricated Roller  
**Hardware:** Standard Plated Steel



\*\* SHOWN WITH OPTIONS \*\*

### ENGINE SPECIFICATIONS

**Manufacturer:** Cummins  
**Type:** 6 Cylinder, Diesel Engine  
**Cooling:** Liquid  
**Performance:** 600 HP @ 2100 RPM  
**Displacement:** 15 Liters  
**Starter:** 12V Electric  
**Fuel Tank:** 330 U.S. Gallons  
**Full Load Operating Time:** 14 Hours

### FEATURES:

**Standard Equipment:** 10" Swing Check Valve, 2 Batteries, Exhaust Rain Cap  
 DOT Gooseneck Trailer, Lockable Fuel Cap, Automatic Liquid Level Control  
**Optional Equipment:** 4 Port Suction, 2 Port Discharge, Butterfly Valves,  
 Auxiliary Fuel Tank, Suction Float Chamber, Gauges,  
 Multiple Fitting Options - Please Ask Your Representative

