

PUMP SPECIFICATIONS

Manufacturer: Cornell
Size: 10"x8" #125
Type: Prime Assisted, Trash Handling
Casing: Ductile Iron
Impeller: Enclosed, 2 vane, Ductile Iron
Solids: 4" Spherical
Impeller Shaft: Stainless Steel 17-4PH
Seal: Mechanical, WC vs SiC
Wear Ring: Cast Iron
Bearings: Heavy duty SKF ball bearing
Hardware: Steel



*shown with options

ENGINE SPECIFICATIONS

Manufacturer: John Deere
Type: 6 Cylinder, Diesel Engine Final tier 4
Cooling: Liquid
Performance: 600 HP @ 2100 RPM
Displacement: 13.5 liters or 823.8205in³
Starter: 12V Electric
Fuel Tank: 330 U.S. Gallons; 15 U.S. Gallons DEF tank
Full Load Operating Time: 12 hours

FEATURES:

Standard Equipment: 8" Swing Check Valve, DOT Goose neck Trailer Kit
 Battery, Exhaust Rain Cap, Lockable Fuel Cap, Automatic liquid level Control.
Optional Equipment: Butterfly Valves, Pressure Gauge, Suction Float Assembly
 Multiple Fitting Options - Please Ask Your Representative

