

### PUMP SPECIFICATIONS

**Manufacturer:** Gorman Rupp  
**Size:** 10"x8" 125# Flanges  
**Type:** Prime Assisted, Trash Handling  
**Casing:** Ductile Iron 65-45-12  
**Impeller:** Enclosed, 2 Vane Ductile Iron  
**Solids:** 3" Spherical  
**Impeller Shaft:** Alloy Steel 4150M  
**Seal:** Mechanical, Oil Lubricated  
**Wear Ring:** Ductile Iron 65-45-12  
**Bearings:** Grease Lubricated Roller  
**Hardware:** Standard Plated Steel



### ENGINE SPECIFICATIONS

**Manufacturer:** Cummins  
**Type:** 6 Cylinder, Turbo charged Diesel Engine  
**Cooling:** Liquid Cooled  
**Performance:** 375HP @ 2000 RPM  
**Displacement:** 9.0 Liters  
**Starter:** 12V Electric  
**Fuel Tank:** 170 U.S. Gallons 9.2 U.S. Gallons DEF  
**Full Load Operating Time:** 9 Hours

\*\*Shown with options

### FEATURES:

**Standard Equipment:** 8" Swing Check Valve, Battery and Box, Exhaust Rain Cap  
 DOT Trailer, Lockable Fuel Cap, Automatic Liquid Level Control  
**Optional Equipment:** 2 Port Suction, 2 Port Discharge, Butterfly Valves,  
 Auxiliary Fuel Tank, Suction Float Chamber, Gauges,  
 Multiple Fitting Options - Please Ask Your Representative

