

### PUMP SPECIFICATIONS

**Manufacturer:** Gorman Rupp  
**Size:** 4" x 4" NPT - Female  
**Type:** Self Priming, Trash Handling  
**Casing:** Ductile iron ASTM A536, 65-45-12  
**Impeller:** 9.75" Ductile iron ASTM A536, 100-70-03  
**Solids:** 3" Spherical  
**Impeller Shaft:** 17-4 PH Stainless Steel  
**Seal:** Oil-Lubricated Mechanical  
**Wear Plate:** Mild Steel  
**Bearings:** Ball bearing  
**Hardware:** Grade 5 Steel

### ENGINE SPECIFICATIONS

**Manufacturer:** Isuzu 4LE2TABW Final Tier4  
**Type:** 4 Cylinder, Diesel Engine  
**Cooling:** Liquid  
**Performance:** 48HP @ 2400 RPM  
**Displacement:** 134 Cu. In. (2.2 liters)  
**Starter:** 12V Electric  
**Fuel Tank:** 80 U.S. Gallons  
**Full Load Operating Time:** 45 Hours



\*\*\*Shown with options

### FEATURES:

**Standard Equipment:** Lifting Bale, Battery, Enclosed Battery Box  
 Exhaust Rain Cap, Lockable Fuel Cap, Murphy Engine Controls  
**Optional Equipment:** Wheel Kit, USDOT Trailer Kit, Hardened Wear Parts  
 Automatic Liquid Level Control, Custom Paint Scheme  
 Multiple Fitting Options - Please Ask Your Representative

