

PUMP SPECIFICATIONS

Manufacturer: Gorman Rupp
Size: 4" x 4" NPT - Female
Type: Self Priming, Trash Handling
Casing: Gray Iron 30
Impeller: Semi-Open, 2 Vane, Ductile Iron
Solids: 3" Spherical
Impeller Shaft: 17-4 PH Stainless Steel
Seal: Oil-Lubricated Mechanical
Wear Plate: 1015 Carbon Steel
Bearings: Open Ball
Hardware: Standard Plated Steel

ENGINE SPECIFICATIONS

Manufacturer: Isuzu 4LE2TABW Final Tier4
Type: 4 Cylinder, Diesel Engine
Cooling: Liquid
Performance: 48HP @ 2400 RPM
Displacement: 134 Cu. In. (2.2 liters)
Starter: 12V Electric
Fuel Tank: 80 U.S. Gallons
Full Load Operating Time: 45 Hours



FEATURES:

Standard Equipment: Lifting Bale, Battery, Enclosed Battery Box
 Exhaust Rain Cap, Lockable Fuel Cap, Murphy Engine Controls
Optional Equipment: Wheel Kit, USDOT Trailer Kit, Hardened Wear Parts
 Automatic Liquid Level Control, Custom Paint Scheme
 Multiple Fitting Options - Please Ask Your Representative

