

PUMP SPECIFICATIONS

Manufacturer: Gorman Rupp
Size: 6" x 6" NPT - Female
Type: Self Priming, Trash Handling
Casing: Gray Iron 30
Impeller: Semi-Open, 2 Vane, Ductile Iron
Solids: 3" Spherical
Impeller Shaft: 17-4 PH Stainless Steel
Seal: Oil-Lubricated Mechanical
Wear Plate: 1015 Carbon Steel
Bearings: Open Ball Oil Lubricated
Hardware: Standard Plated Steel

ENGINE SPECIFICATIONS

Manufacturer: Isuzu 4JJITABW Final Tier4
Type: 4 Cylinder, Diesel Engine
Cooling: Liquid
Performance: 70HP @ 2000 RPM
Displacement: 183 Cu. In. (3.0L)
Starter: 12V Electric
Fuel Tank: 100 gallons
Full Load Operating Time: 37 HOURS



FEATURES:

Standard Equipment: Lifting Bale, Battery, Enclosed Battery Box
 Exhaust Rain Cap, Lockable Fuel Cap, Murphy Engine Controls
Optional Equipment: Wheel Kit, USDOT Trailer Kit, Hardened Wear Parts
 Automatic Liquid Level Control, Custom Color Scheme
 Multiple Fitting Options - Please Ask Your Representative

